

KERN EW 220-3NM

KERN

The classic balance with robust tuning fork measuring system



Category

Brand	KERN
Product category	Laboratory balance
Product group	Precision balance
Product family	EW

Measuring System

Construction type of the scale	Single-range balance
Weighing system	Tuning fork
Weighing capacity [Max]	220 g
Readability [d]	0,001 g
Reproducibility	0,001 g
Linearity	± 0,002 g
USP Minimum weight of sample (k = 2, U = 0.1%)	2 g
Resolution	220.000
Adjustment options	Adjusting with external weight
Recommended adjusting weight	200 g (F1)
Stabilization time	2 s
Warm-up time	120 min
Eccentric loading at 1/3 [Max]	0,003 g
Maximum creep (15 minutes)	10 mg
Maximum creep (30 minutes)	20 mg
Default unit	g
Units	g dwt tl (Tw) tl (HK) ozt tl (Singap, Malays) ct lb

oz
to
mom

Display

Display type	LCD
Display backlight	✓
Display screen size	109×22 mm
Display digit height	17 mm
Languages of the user interface	Symbol language

Construction

Dimension housing (W×D×H)	180×235×75 mm
Dimensions completely mounted (W×D×H)	185×235×165 mm
Dimensions rectangular draught shield - inner (W×D×H)	158×130×78 mm
Dimensions rectangular draught shield - outer (W×D×H)	174×144×105 mm
Dimensions weighing surface (Ø)	118 mm
Dimensions weighing surface	118 mm
Material housing	plastic
Material weighing plate	stainless steel
Material draught shield	plastic
Level indicator	✓
Levelling feet adjustable	✓
Draught shield optional	no

Functions

Percentage determination	✓
Tolerance weighing	✓
Tolerance weighing - type of signal	visual
Underfloor weighing	Eye (optional)
Capacity - Display	✓
Counting function	✓
Counting resolution (laboratory conditions)	220.000
Smallest piece weight when piece counting - laboratory conditions	1 mg
Smallest piece weight when piece counting - normal conditions	10 mg
Reference quantity	10, 30, 50, 100
Auto-off interval(s) in battery mode/rechargeable battery mode	3 min
Auto-off interval(s) in mains power mode	3 min
Tare function	manual (multi)
Number of keys for operation	5

KERN EW 220-3NM

KERN

The classic balance with robust tuning fork measuring system

Interface

Interfaces	RS-232 standard
------------	-----------------

Power Supply

Supplied power supply	Power supply unit
Plug-in power supply type	Power adapter
Plug-in power supply / adapter for countries - included with the delivery	EURO UK US CH
Plug-in power supply / adapter for countries - optional	EURO AUS UK US CH
Input voltage power supply / power [Max]	220 V - 240 V AC, 50 Hz
Input voltage device / power [Max]	12 V, 1 A
Battery / accumulator type	NiCd
Rechargeable battery	EG-A04
Rechargeable battery operating time - backlight on	12 h
Rechargeable battery charging time	12 h
Rechargeable battery optional	Rchrg. battery optional

Environmental conditions

Ambient temperature [Min]	10 °C
Ambient temperature [Max]	30 °C
Humidity of environment [Max]	80 %
Storage temperature [Min]	-20 °C
Storage temperature [Max]	60 °C

Approval

CE mark	✓
---------	---

Services (optional)

Article number for DAkkS calibration	963-127
Article number for certificate of conformity	969-517

Packing & Shipping


Delivery time	1 d
Dimensions packaging (W×D×H)	400×320×220 mm
Shipping method	Parcel service
Net weight approx.	1,4 kg
Gross weight approx.	3,0 kg

Shipping weight

5,6 kg

Pictograms

STANDARD



OPTION

