## KERN ABT 220-4NM



#### The premium model with single-cell weighing system



### Category

Brand	KERN
Product categoriy	Laboratory balance
Product group	Analytical balance
Product family	ABT

#### Measuring System

weasuring System	
Construction type of the scale	Single-range balance
Weighing system	Single-Cell
Weighing capacity [Max]	220 g
Weighing capacity [Max] (ct)	1100 ct
Readability [d]	0,0001 g
Readability carat [d] (ct)	0,001 ct
Reproducibility	0,0001 g
Linearity	± 0,0002 g
USP Minimum weight of sample (k = 2, U = 0.1%)	200 mg
Minimum weight [Min]	0,01 g
Minimum weight [Min] (ct)	0,1 ct
Resolution	2.200.000
Tare range	220 g
Adjustment options	Internal calibration (automatic) Adjusting with internal weight (manual)
Automatic adjustment - Standard temperature deviation	0,5 °C
Automatic adjustment - Standard time interval	4 h
Stabilization time	4 s
Warm-up time	8 h
Eccentric loading at 1/3 [Max]	0,0003 g
Default unit	g

Units	g
Liste (for device in a suffermation	ct
Units (if device is conformity assessed)	g ct
Conformity assessment possible	$\checkmark$
Display	
Display type	LCD
Display digit height	14 mm
Construction	
Dimension housing (W×D×H)	217×345×330 mm
Dimensions rectangular draught shield - inner (W×D×H)	168×172×223 mm
Dimensions rectangular draught shield - outer (W×D×H)	200×240×260 mm
Dimensions weighing surface (Ø)	80 mm
Dimensions weighing surface	80 mm
Material housing	metal
Material weighing plate	stainless steel
Material draught shield	glass
Material display housing	Plastics
Level indicator	$\checkmark$
Levelling feet adjustable	
	$\checkmark$
Functions	·
-	✓ ✓
Functions	
Functions Sum memory function	✓
Functions Sum memory function Recipe/summing level	✓ Rez A (Net total)
Functions Sum memory function Recipe/summing level Percentage determination	✓ Rez A (Net total) ✓ Hook (included in
Functions Sum memory function Recipe/summing level Percentage determination Underfloor weighing Function for averaging under	✓ Rez A (Net total) ✓ Hook (included in delivery)
Functions Sum memory function Recipe/summing level Percentage determination Underfloor weighing Function for averaging under unstable weighing conditions	✓ Rez A (Net total) ✓ Hook (included in delivery)
Functions Sum memory function Recipe/summing level Percentage determination Underfloor weighing Function for averaging under unstable weighing conditions Capacity - Display	✓ Rez A (Net total) ✓ Hook (included in delivery) ✓
Functions Sum memory function Recipe/summing level Percentage determination Underfloor weighing Function for averaging under unstable weighing conditions Capacity - Display Standby function	✓ Rez A (Net total) ✓ Hook (included in delivery) ✓ ✓
Functions Sum memory function Recipe/summing level Percentage determination Underfloor weighing Function for averaging under unstable weighing conditions Capacity - Display Standby function Counting function Counting resolution (laboratory	✓ Rez A (Net total) ✓ Hook (included in delivery) ✓ ✓ ✓
Functions Sum memory function Recipe/summing level Percentage determination Underfloor weighing Function for averaging under unstable weighing conditions Capacity - Display Standby function Counting function Counting resolution (laboratory conditions) Counting reference weight can be	✓ Rez A (Net total) ✓ Hook (included in delivery) ✓ ✓ ✓ ✓ ✓ Z20.000
Functions Sum memory function Recipe/summing level Percentage determination Underfloor weighing Function for averaging under unstable weighing conditions Capacity - Display Standby function Counting function Counting resolution (laboratory conditions) Counting reference weight can be entered Smallest piece weight when piece	✓ Rez A (Net total) ✓ Hook (included in delivery) ✓ ✓ ✓ 220.000
Functions Sum memory function Recipe/summing level Percentage determination Underfloor weighing function for averaging under unstable weighing conditions Capacity - Display Standby function Counting function Counting resolution (laboratory conditions) Counting reference weight can be entered Smallest piece weight when piece counting - laboratory conditions	✓ Rez A (Net total) ✓ Hook (included in delivery) ✓ ✓ ✓ 220.000 ✓ 1 mg
Functions Sum memory function Recipe/summing level Percentage determination Underfloor weighing Underfloor weighing under unstable weighing conditions Capacity - Display Standby function Counting function Counting resolution (laboratory conditions) Counting reference weight can be entered Smallest piece weight when piece counting - normal conditions	✓ Rez A (Net total) ✓ Hook (included in delivery) ✓ ✓ ✓ 220.000 ✓ 1 mg 10 mg
Functions Sum memory function Recipe/summing level Percentage determination Underfloor weighing Function for averaging under unstable weighing conditions Capacity - Display Standby function Counting function Counting resolution (laboratory conditions) Counting reference weight can be entered Smallest piece weight when piece counting - normal conditions Reference quantity	<ul> <li>✓</li> <li>Rez A (Net total)</li> <li>✓</li> <li>Hook (included in delivery)</li> <li>✓</li> <li>✓</li></ul>

# KERN ABT 220-4NM



The premium model with single-cell weighing system

Interface	
Interfaces	RS-232 standard
Power Supply	
Supplied power supply	Power supply unit
Plug-in power supply type	Power adapter
Plug-in power supply / adapter for countries - included with the delivery	EURO AUS UK US CH
Plug-in power supply / adapter for countries - optional	EURO AUS UK US CH
Input voltage power supply / power [Max]	220 V - 240 V AC, 50 Hz
Input voltage device / power [Max]	12 V DC, 1000 mA
Environmental conditions	
Ambient temperature [Min]	10 °C
Ambient temperature [Max]	30 °C
Humity of environment [Max]	80 %
Storage temperature [Min]	-10 °C
Storage temperature [Max]	50 °C
Approval	
CE mark	1
Conformity assessment possible ex works	1
Accuracy classe	1
Verification scale interval [e]	0,001 g
Verification scale interval [e] (ct)	0,01 ct
Services (optional)	
Article number for conformity assessment	965-201
Article number for DAkkS calibration	963-101
Article number for certificate of conformity	969-517
Packing & Shipping	
Delivery time	1 d
Dimensions packaging (W×D×H)	400×585×545 mm
Shipping method	Parcel service
Net weight approx.	8 kg

Gross weight approx.	12 kg
Shipping weight	25,5 kg

### Pictograms

#### STANDARD



SC TECH 1 DAY

OPTION



FACTORY

