

KERN ABT 320-4NM

The premium model with single-cell weighing system

KERN



Category

Brand	KERN
Product category	Laboratory balance
Product group	Analytical balance
Product family	ABT

Measuring System

Construction type of the scale	Single-range balance
Weighing system	Single-Cell
Weighing capacity [Max]	320 g
Weighing capacity [Max] (ct)	1600 ct
Readability [d]	0,0001 g
Readability carat [d] (ct)	0,001 ct
Reproducibility	0,00015 g
Linearity	± 0,0003 g
USP Minimum weight of sample (k = 2, U = 0.1%)	300 mg
Minimum weight [Min]	0,01 g
Minimum weight [Min] (ct)	0,1 ct
Resolution	3.200.000
Tare range	320 g

Adjustment options	Internal calibration (automatic) Adjusting with internal weight (manual)
--------------------	---

Automatic adjustment - Standard temperature deviation	0,5 °C
---	--------

Automatic adjustment - Standard time interval	4 h
---	-----

Stabilization time	4 s
--------------------	-----

Warm-up time	8 h
--------------	-----

Eccentric loading at 1/3 [Max]	0,0003 g
--------------------------------	----------

Default unit	g
--------------	---

Units	g ct
-------	---------

Units (if device is conformity assessed)	g ct
--	---------

Conformity assessment possible	✓
--------------------------------	---

Display

Display type	LCD
--------------	-----

Display digit height	14 mm
----------------------	-------

Construction

Dimension housing (W×D×H)	217×356×337 mm
---------------------------	----------------

Dimensions rectangular draught shield - inner (W×D×H)	168×172×223 mm
---	----------------

Dimensions rectangular draught shield - outer (W×D×H)	200×240×260 mm
---	----------------

Dimensions weighing surface (Ø)	80 mm
---------------------------------	-------

Dimensions weighing surface	80 mm
-----------------------------	-------

Material housing	metal
------------------	-------

Material weighing plate	stainless steel
-------------------------	-----------------

Material draught shield	glass
-------------------------	-------

Material display housing	Plastics
--------------------------	----------

Level indicator	✓
-----------------	---

Levelling feet adjustable	✓
---------------------------	---

Functions

Sum memory function	✓
---------------------	---

Recipe/summing level	Rez A (Net total)
----------------------	-------------------

Percentage determination	✓
--------------------------	---

Underfloor weighing	Hook (included in delivery)
---------------------	-----------------------------

Function for averaging under unstable weighing conditions	✓
---	---

Capacity - Display	✓
--------------------	---

Standby function	✓
------------------	---

Counting function	✓
-------------------	---

Counting resolution (laboratory conditions)	320.000
---	---------

Counting reference weight can be entered	✓
--	---

Smallest piece weight when piece counting - laboratory conditions	1 mg
---	------

Smallest piece weight when piece counting - normal conditions	10 mg
---	-------

Reference quantity	10, 20, 50, 100
--------------------	-----------------

Tare function	manual (multi)
---------------	----------------

Number of keys for operation	6
------------------------------	---

KERN ABT 320-4NM

The premium model with single-cell weighing system

KERN

Interface

Interfaces	RS-232 standard
------------	-----------------

Power Supply

Supplied power supply	Power supply unit
-----------------------	-------------------

Plug-in power supply type	Power adapter
---------------------------	---------------

Plug-in power supply / adapter for countries - included with the delivery	EURO AUS UK US CH
---	-------------------------------

Plug-in power supply / adapter for countries - optional	EURO AUS UK US CH
---	-------------------------------

Input voltage power supply / power [Max]	220 V - 240 V AC, 50 Hz
--	-------------------------

Input voltage device / power [Max]	12 V DC, 1000 mA
------------------------------------	------------------

Environmental conditions

Ambient temperature [Min]	10 °C
---------------------------	-------

Ambient temperature [Max]	30 °C
---------------------------	-------

Humidity of environment [Max]	80 %
-------------------------------	------

Storage temperature [Min]	-10 °C
---------------------------	--------

Storage temperature [Max]	50 °C
---------------------------	-------

Approval

CE mark	✓
---------	---

Conformity assessment possible ex works	✓
---	---

Accuracy classe	I
-----------------	---

Verification scale interval [e]	0,001 g
---------------------------------	---------

Verification scale interval [e] (ct)	0,01 ct
--------------------------------------	---------

Services (optional)

Article number for conformity assessment	965-201
--	---------

Article number for DAkkS calibration	963-101
--------------------------------------	---------

Article number for certificate of conformity	969-517
--	---------

Packing & Shipping

Delivery time	1 d
---------------	-----

Dimensions packaging (W×D×H)	405×580×550 mm
------------------------------	----------------

Shipping method	Parcel service
-----------------	----------------

Net weight approx.	8 kg
--------------------	------

Gross weight approx.	12 kg
----------------------	-------

Shipping weight	25,8 kg
-----------------	---------

Pictograms

STANDARD



OPTION



FACTORY

