KERN ACJ 300-4M



The bestseller in analytical balances, with high-quality single-cell weighing system, verification optional



С	at	е	g	0	rv
			\odot		

Brand	KERN
Product categoriy	Laboratory balance
Product group	Analytical balance
Product family	ACJ

Measuring System

Measuring System	
Construction type of the scale	Single-range balance
Weighing system	Single-Cell
Weighing capacity [Max]	320 g
Weighing capacity [Max] (ct)	1600 ct
Readability [d]	0,0001 g
Readability carat [d] (ct)	0,001 ct
Reproducibility	0,0002 g
Linearity	± 0,0003 g
USP Minimum weight of sample (k = 2, U = 0.1%)	400 mg
Minimum weight [Min]	0,01 g
Minimum weight [Min] (ct)	0,1 ct
Resolution	3.200.000
Adjustment options	Internal calibration (automatic) Adjusting with internal weight (manual)
Recommended adjusting weight	300 g (E2)
Automatic adjustment - Standard temperature deviation	2 °C
Automatic adjustment - Standard time interval	4 h
Stabilization time	3 s
Warm-up time	8 h
Eccentric loading at 1/3 [Max]	0,0005 g
Default unit	g

Units	g	
Onits	mg ct	
	g	
Units (if device is conformity assessed)	mg	
assessed)	ct	
Conformity assessment possible	✓	
Diaplay		
Display		
Display type	LCD	
Display type	LCD	
Display backlight	no	
Display screen size	115×32 mm	
Display digit height	14 mm	
Languages of the user interface	Symbol language	
Construction		
Dimension housing (W×D×H)	213×333×338 mm	
Dimensions rectangular draught	174×162×227 mm	
shield - inner (W×D×H)		
Dimensions rectangular draught shield - outer (W×D×H)	201×220×256 mm	
Dimensions weighing surface (Ø)	91 mm	
Dimensions weighing surface	91 mm	
	7 1 11111	
Material housing	cast aluminium, plastic	
Material housing	cast aluminium, plastic	
Material housing Material weighing plate	cast aluminium, plastic stainless steel	
Material housing Material weighing plate Material draught shield	cast aluminium, plastic stainless steel glass	
Material housing Material weighing plate Material draught shield Material display housing	cast aluminium, plastic stainless steel glass	
Material housing Material weighing plate Material draught shield Material display housing Level indicator	cast aluminium, plastic stainless steel glass Plastics ✓	
Material housing Material weighing plate Material draught shield Material display housing Level indicator Levelling feet adjustable Functions	cast aluminium, plastic stainless steel glass Plastics ✓	
Material housing Material weighing plate Material draught shield Material display housing Level indicator Levelling feet adjustable Functions Sum memory function	cast aluminium, plastic stainless steel glass Plastics ✓ ✓	
Material housing Material weighing plate Material draught shield Material display housing Level indicator Levelling feet adjustable Functions Sum memory function Recipe/summing level	cast aluminium, plastic stainless steel glass Plastics ✓ ✓ Rez A (Net total)	
Material housing Material weighing plate Material draught shield Material display housing Level indicator Levelling feet adjustable Functions Sum memory function Recipe/summing level Percentage determination	cast aluminium, plastic stainless steel glass Plastics ✓ ✓ Rez A (Net total)	
Material housing Material weighing plate Material draught shield Material display housing Level indicator Levelling feet adjustable Functions Sum memory function Recipe/summing level Percentage determination Tolerance weighing	cast aluminium, plastic stainless steel glass Plastics ✓ ✓ Rez A (Net total) ✓	
Material housing Material weighing plate Material draught shield Material display housing Level indicator Levelling feet adjustable Functions Sum memory function Recipe/summing level Percentage determination Tolerance weighing - type of signal	cast aluminium, plastic stainless steel glass Plastics ✓ ✓ Rez A (Net total) ✓ visual	
Material housing Material weighing plate Material draught shield Material display housing Level indicator Levelling feet adjustable Functions Sum memory function Recipe/summing level Percentage determination Tolerance weighing Tolerance weighing - type of signal Standby function	cast aluminium, plastic stainless steel glass Plastics ✓ ✓ Rez A (Net total) ✓ visual	
Material housing Material weighing plate Material draught shield Material display housing Level indicator Levelling feet adjustable Functions Functions Sum memory function Recipe/summing level Percentage determination Tolerance weighing - type of signal Standby function Counting function	cast aluminium, plastic stainless steel glass Plastics ✓ ✓ Kez A (Net total) ✓ visual ✓	
Material housing Material weighing plate Material draught shield Material display housing Level indicator Levelling feet adjustable Functions Sum memory function Recipe/summing level Percentage determination Tolerance weighing Tolerance weighing - type of signal Standby function	cast aluminium, plastic stainless steel glass Plastics ✓ ✓ Rez A (Net total) ✓ visual	
Material housing Material weighing plate Material draught shield Material display housing Level indicator Levelling feet adjustable Functions Sum memory function Recipe/summing level Percentage determination Tolerance weighing Tolerance weighing - type of signal Standby function Counting function (laboratory	cast aluminium, plastic stainless steel glass Plastics ✓ ✓ Kez A (Net total) ✓ visual ✓	
Material housing Material weighing plate Material draught shield Material display housing Level indicator Levelling feet adjustable Functions Sum memory function Recipe/summing level Percentage determination Tolerance weighing - type of signal Standby function Counting function Counting resolution (laboratory conditions) Counting reference weight can be entered	cast aluminium, plastic stainless steel glass Plastics ✓ ✓ Kez A (Net total) ✓ visual ✓ ✓ 320.000	
Material housing Material weighing plate Material draught shield Material display housing Level indicator Levelling feet adjustable Functions Sum memory function Recipe/summing level Percentage determination Percentage determination Tolerance weighing - type of signal Standby function Counting function Counting resolution (laboratory conditions) Counting reference weight can be entered Smallest piece weight when piece counting - laboratory conditions	cast aluminium, plastic stainless steel glass Plastics ✓ ✓ ✓ Rez A (Net total) ✓ visual ✓ 320.000	
Material housing Material weighing plate Material draught shield Material display housing Level indicator Levelling feet adjustable Functions Sum memory function Recipe/summing level Percentage determination Tolerance weighing - type of signal Standby function Counting function Counting resolution (laboratory conditions) Counting reference weight can be entered	cast aluminium, plastic stainless steel glass Plastics ✓ ✓ ✓ Kez A (Net total) ✓ visual ✓ 320.000	

KERN ACJ 300-4M



The bestseller in analytical balances, with high-quality single-cell weighing system, verification optional

Number of keys for operation	0 - 99 min manual (multi) 6	
Interface		
Interfaces	RS-232 standard USB-Device	
Power Supply		
Supplied power supply Plug-in power supply type	Power supply unit Power adapter	
Plug-in power supply / adapter for countries - included with the delivery	EURO UK US CH	
Plug-in power supply / adapter for countries - optional	EURO UK US CH	
Input voltage power supply / power [Max]	110 V - 230 V AC	
Input voltage device / power [Max]	12 V, 1 A	
Environmental conditions		
Ambient temperature [Min]	10 °C	
Ambient temperature [Max]	30 °C	
Humity of environment [Min]	20 %	
Humity of environment [Max]	85 %	
Storage temperature [Min]	-10 °C	
Storage temperature [Max]	50 °C	
Approval		
CE mark	1	
Conformity assessment possible ex works	\checkmark	
Accuracy classe	I	
Verification scale interval [e]	0,001 g	
Verification scale interval [e] (ct)	0,01 ct	
Services (optional)		
Services (optional) Article number for conformity assessment	965-201	
Article number for conformity	965-201 963-101	

Packing & Shipping		
Delivery time	1 d	
Dimensions packaging (W×D×H)	390×570×530 mm	
Shipping method	Parcel service	
Net weight approx.	7 kg	
Gross weight approx.	9 kg	
Shipping weight	23,6 kg	

Pictograms

STANDARD



OPTION

DAkkS

+3 DAYS

FACTORY

