KERN **PBJ 8200-1M**



Multifunctional laboratory balance with single-cell weighing system, verification optional



Category	
Brand	KERN
Product categoriy	Laboratory balance
Product group	Precision balance
Product family	PBJ

Measuring System	
Construction type of the scale	Single-range balance
Weighing system	Single-Cell
Weighing capacity [Max]	8200 g
Readability [d]	0,1 g
Reproducibility	0,1 g
Linearity	± 0,2 g
USP Minimum weight of sample (k = 2, U = 0.1%)	200 g
Minimum weight [Min]	5 g
Resolution	82.000
Adjustment options	Internal calibration (automatic)
Automatic adjustment - Standard temperature deviation	1 °C
Automatic adjustment - Standard time interval	4 h
Stabilization time	1,2 s
Warm-up time	120 min
Eccentric loading at 1/3 [Max]	0,5 g
Default unit	g
Units	kg g ct
Units (if device is conformity assessed)	kg g
Conformity assessment possible	✓

Display	
Display type	LCD
Display backlight	✓
Display digit height	14 mm

Construction	
Dimension housing (W×D×H)	210×330×78 mm
Dimensions weighing surface (W×D)	180×190 mm
Dimensions weighing surface	180×190 mm
Dimensions weighing platform (W×D×H)	180×195×8 mm
Material housing	cast aluminium
Material weighing plate	stainless steel
Material display housing	Plastics
Level indicator	✓
Levelling feet adjustable	✓

Functions	
PreTare function	✓
Recipe/summing level	Rez A (Net total)
Percentage determination	✓
Dispensing function	✓
Density determination	✓
Tolerance weighing	✓
Tolerance weighing - type of signal	visual
Underfloor weighing	Hook (included in delivery)
Function for averaging under unstable weighing conditions	✓
Time display	✓
Capacity - Display	✓
Standby function	✓
Counting function	✓
Counting resolution (laboratory conditions)	82.000
Smallest piece weight when piece counting - laboratory conditions	100 mg
Smallest piece weight when piece counting - normal conditions	1 g
Reference quantity	10, 25, 50, 100, n (any number of pieces)
Peak function	✓
Tare function	manual (multi)
Number of keys for operation	6

Interface	
Interfaces	RS-232 standard

1

KERN **PBJ 8200-1M**



Multifunctional laboratory balance with single-cell weighing system, verification optional

Power Supply	
Supplied power supply	Power supply unit
Plug-in power supply / adapter for countries - included with the delivery	EURO UK US CH
Plug-in power supply / adapter for countries - optional	EURO AUS UK US CH
Input voltage power supply / power [Max]	100 V - 240 V AC, 50 / 60 Hz
Input voltage device / power [Max]	12 V DC, 1000 mA

Environmental conditions	
Ambient temperature [Min]	10 °C
Ambient temperature [Max]	30 °C
Humity of environment [Max]	80 %
Storage temperature [Min]	-10 °C
Storage temperature [Max]	50 °C

Approval	
CE mark	✓
Conformity assessment possible ex works	✓
Accuracy classe	II
Verification scale interval [e]	1 g

Services (optional)	
Article number for conformity assessment	965-217
Article number for DAkkS calibration	963-128
Article number for certificate of conformity	969-517

Packing & Shipping	
Delivery time	1 d
Dimensions packaging (W×D×H)	370×455×265 mm
Shipping method	Parcel service
Net weight approx.	5,0 kg
Gross weight approx.	7 kg
Shipping weight	8,9 kg



