## KERN ACJ 80-4M



The bestseller in analytical balances, with high-quality single-cell weighing system, verification optional



Category	
Brand	KERN
Product categoriy	Laboratory balance
Product group	Analytical balance
Product family	ACJ

Measuring System	
Construction type of the scale	Single-range balance
Weighing system	Single-Cell
Weighing capacity [Max]	82 g
Readability [d]	0,0001 g
Reproducibility	0,0002 g
Linearity	± 0,0003 g
USP Minimum weight of sample (k = 2, U = 0.1%)	400 mg
Minimum weight [Min]	0,01 g
Resolution	820.000
Adjustment options	Internal calibration (automatic) Adjusting with internal weight (manual)
Recommended adjusting weight	80 g (E2)
Automatic adjustment - Standard temperature deviation	2 °C
Automatic adjustment - Standard time interval	4 h
Stabilization time	3 s
Warm-up time	4 h
Eccentric loading at 1/3 [Max]	0,0005 g
Default unit	g
Units	g mg

Units (if device is conformity	g
assessed)	mg
Conformity assessment possible	✓

Display	
Display type	LCD
Display type	LCD
Display backlight	no
Display screen size	115×32 mm
Display digit height	14 mm
Languages of the user interface	Symbol language

Construction	
Dimension housing (W×D×H)	213×333×338 mm
Dimensions rectangular draught shield - inner (W×D×H)	174×162×227 mm
Dimensions rectangular draught shield - outer (W×D×H)	201×220×256 mm
Dimensions weighing surface (Ø)	91 mm
Dimensions weighing surface	91 mm
Material housing	cast aluminium, plastic
Material weighing plate	stainless steel
Material draught shield	glass
Material display housing	Plastics
Level indicator	✓
Levelling feet adjustable	✓

Sum memory function  Recipe/summing level  Percentage determination  ✓  Tolerance weighing	(Net total)
Percentage determination	(Net total)
•	(INCL LOLAI)
olerance weighing	
olerance weighing - type of signal visual	
Standby function 🗸	
Counting function 🗸	
Counting resolution (laboratory 82.00 conditions)	00
Counting reference weight can be entered	
Smallest piece weight when piece counting - laboratory conditions 1 mg	
Smallest piece weight when piece counting - normal conditions	g
Reference quantity 5, 10,	, 20, 50, 100
Auto-off interval(s) in mains power 0 - 99	min
are function manu	al (multi)
Number of keys for operation 6	

1

## KERN ACJ 80-4M



The bestseller in analytical balances, with high-quality single-cell weighing system, verification optional

Interface	
Interfaces	RS-232 standard USB-Device

	O3D-Device
Power Supply	
Supplied power supply	Power supply unit
Plug-in power supply type	Power adapter
Plug-in power supply / adapter for countries - included with the delivery	EURO UK US CH
Plug-in power supply / adapter for countries - optional	EURO UK US CH
Input voltage power supply / power [Max]	110 V - 230 V AC
Input voltage device / power [Max]	12 V, 1 A

Environmental conditions	
Ambient temperature [Min]	10 °C
Ambient temperature [Max]	30 °C
Humity of environment [Min]	20 %
Humity of environment [Max]	85 %
Storage temperature [Min]	-10 °C
Storage temperature [Max]	50 °C

Approval	
CE mark	✓
Conformity assessment possible ex works	✓
Accuracy classe	1
Verification scale interval [e]	0,001 g

Services (optional)	
Article number for conformity assessment	965-201
Article number for DAkkS calibration	963-101
Article number for certificate of conformity	969-517

Packing & Shipping	
Delivery time	1 d
Dimensions packaging (W×D×H)	390×565×520 mm
Shipping method	Parcel service
Net weight approx.	7 kg
Gross weight approx.	9 kg

Shipping weight					22,9 kg				
Picto	grams								
STANDARD									
CAL INT	RS 232	USB	GLP PRINTER	PCS	A RECIPE	0/ 0 PERCENT	CUNIT	-√+ ⑤ TOL	

В	E I	
MULTI	SC TECH	1 DAY

**OPTION** 



**FACTORY** 

